

SYM	ECN	DESCRIPTION	DATE	APPROVED

RoHS
compliant

Technical Data

Contact:	brass JIS C2700(CuZn35)
Contact plating:	see ordering information
Insulator:	black glass filled polyester

Insulator:

brass JIS C2700(CuZn35)
see ordering information
black glass filled polyester

Current rating: 2Amps

Voltage rating: 125V

Contact resistance: 20mΩ max.

Insulation resistance: 1000M Ω min. at 500V/minute





Withstanding Voltage: 1000V AC/minute

Retention force: 0.85Kgf/contact min.

Operating temperature: -55°C to $+105^{\circ}\text{C}$

Soldering temperature: $260^{\circ}\text{C} \pm 5^{\circ}$ 10S

Critical Dimensions: ▼



Ordering information

BFD	XX	-	X	X	B
-----	----	---	---	---	---

38

natconn® 广东纳特康电子股份有限公司
GUANGDONG NATCONN ELECTRONIC CO.,LTD

GUANGDONG NATCONN ELECTRONIC CO.,LTD

No. of Positions	Series No.
04-50	01-999

Plating Option	Insulator Material Option
A. G/F	E BK-ICP
B. Ausp*	G BK-PAET
C. Ausp*	S Special
D. Aut/f*	(Underline option is standard)
H AF/ST 20p*	
S Sn 120p	
Z Special	
(Underline option is standard)	

Packing		TOLERANCE:		PROJECTION		TITLE:	
1.General		ANGLE ±2°				Pitch:2.00*2.00mm Box Header	
2.Taped&Reel		X.XXX ±0.05		DATE	2018/12/24	SMT Type,MX2.0 Header	
3.Tube	✓	X.XX ±0.20		DRAWN	唐建平	CUSTOMER:	N/A
4.Tray		X.X ±0.30		CHECKED	雷邦军	PART NO.:	N/A
5.Other		X. ±0.50		APPROVED	冯显东	SIZE:	A4
						UNIT:	mm
						SCALE:	1:1
						SHEET:	1/1